# STEP<sub>®</sub>

Shanghai Yixin International Trade Co., Ltd. NO.599 Meiyu Road, Jiading District, Shanghai

Zip: 201802

TEL: 86-21-3101 0622 FAX: 86-21-3101 0649

Shanghai STEP Electric Corporation

NO.599 Meiyu Road, Jiading District, Shanghai

Shanghai STEP Robotics Co., Ltd.

NO.599 Meiyu Road, Jiading District, Shanghai

Zip: 201802

Shanghai Sigriner STEP Electric Co., Ltd.

NO.1560 Siyi Road, Jiading District, Shanghai

Zip: 201801

Shanghai STEP Cable Technology Co., Ltd.

NO.289 Xinqin Road, Jiading District, Shanghai

Zip: 201802

Shenzhen ADTECH Technology Co., Ltd.

5/F, Nanshan District, Yiyuan Road Majialong IC Industry Park,

Zip: 518052

Shanghai STEP Automotive Equipment Co., Ltd. NO.66 Shenxu Road, Songjiang District, Shanghai

Shanghai Huitong Automation Technology Development Co., Ltd. Room 3503-3504, CITIC Plaza, No.859, North Sichuan Road,

Shanghai Zip: 200085

Hangzhou Zhishan Intelligent Control Technology Co., Ltd. NO.9 Xianxin Road, Xianlin Industry Park, Yuhang District,

Hangzhou, Zhejiang Zip: 311112

STEP Sigriner Elektronik Gmbh

Martin-Moser-str. 15, 84503 Altoetting, Germany

HONG KONG Inernational STEP Holdings Co., Ltd.
Unit AD, 9/F, Nathan Commercial Building, 430-436 Nathan Road, Kowloon, Hong Kong

SIGRINER Automation (Mfg ) Sdn.Bhd.

Lot 5, Japan Asam Jawa 16/15, Section 16, 40200 Shah Alam, Selangor Darul Ehsan,

STEP-SIGRINER DO BRASIL

Rua Alvaro Fragoso, 96-Vila Carioca – Sao Paulo, SP, Brasil CEP 04223-000





Shanghai Yixin International Trade Co,Ltd. was found in April 2011, which is a wholly-owned subsidiary of Shanghai STEP Electric Corporation.

Yixin International is a comprehensive international trading company with multilanguage support of business, including English, Russian, Spanish, German, Japanese and so on. As an elevator part integrated supplier, we provide professional lift solutions. We cooperate with partners from more than 50 different countries such as Germany, Malaysia, Vietnam, Indonesia, Russia, Singapore, Australia, India, Turkey and so on.



Our company creates a globa advantage by means of good service.

We have established overseas wholly owned subsidiaries, namely STEP Sigriner Elektronik GmbH in Germany and Hong Kong International STEP Holdings Co., Ltd. as well as two subsidiary joint-venture companies STEP-Sigriner DO BRASIL in Brazil and Sigriner Automation (MFG) SDN. BHD.in Malaysia.



The Middle East and Southeast Asia region have also been in the selection process, planning to set up offices in the coming year. Yixin will continue to expand the business scope all over the world.

Company Information



## **Contents**

Company Information

02 Contents 04 Traction Machine 08 Door System

3 Safety Components Series


Guidance System

 $\underset{\text{Others}}{25}$ 

32 Cabin


**STEP Spirit:** Strive for global competitiveness, pursue the best practice and always stay ahead of the industry.





# Traction Machine

# Permanent Mangnet Synchronous Gearless Traction Machine



V	oltage	380V
F	Roping	2:1
	Wrap	Single
El	v. Load	320~1600kg
Elv	. Speed	0.5~2.5m/s
She	ave Diam	320~480mm
	Duty	S5-40%ED
IF	<sup>o</sup> Code	IP41
Ins		F



# Permanent Mangnet Synchronous Gearless Traction Machine



Voltage	380V
Roping	2:1/1:1(320~400kg)
Wrap	Single
Elv. Load	320~2500kg
Elv. Speed	0.4~1.75m/s
Sheave Diam	200~480mm
Duty	S5-40%ED
IP Code	IP41
Ins. Class	F


#### **Geared Traction Machine**





Voltage	380V
Roping	1:1
Elv. Load	100~2500kg
Elv. Speed	0.4~2.0m/s

06



# **Door System**

#### **Center Opening Door Operator** (PM & VVVF)



Wide: 600~1200mm;

Installation: Top installation & Car frame Installation

#### **Center Opening Landing Door Device**



Wide: 600~1200mm

**Center Opening** (Fire proof & Insulated door) **Landing Door Device** 



Wide: 700~1200mm

### $\textbf{Side Opening Door Operator} \ \ (\textbf{PM \& VVVF})$



Wide: 700~1300mm;

Installation: Top installation & Car frame Installation

#### **Side Opening Landing Door Device**



Wide: 700~1300mm

#### Side Opening (Fire proof & Insulated door ) Landing Door Device



Wide: 700~1300mm

#### **4 Panels Center Opening Door Operator**



Wide: 700~3000mm;

Installation: Top installation & Car frame Installation

# 4 Panels Center Opening Landing Door Device



Wide: 700~3000mm

## **Door System**

# 3 Panels Side Opening PM Door Operator



Wide: 900~1800mm;

Installation: Top installation & Car frame Installation

# 3 Panels Side Opening Landing Door Device



Wide: 900~1800mm



#### **Overspeed Governor**



Governor Non-Return

Speed: ≤0.63m/s; 0.75m/s;1.0m/s;1.5~1.6m/s;1.75m/s; 2.0m/s; 2.5m/s

Sheave diameter: φ240

Wire Rope Nominal diameter: Standard φ8mm, Optional φ6mm

Braking Force: 800N~1500N



Two Way Governor

Speed: ≤0.63m/s;1.0m/s;1.5~1.6m/s;1.75m/s; 2.0m/s; 2.5m/s

Sheave diameter: \$\phi\$ 240

Wire Rope Nominal diameter: Standard \$ 8mm, Optional \$ 6mm

Braking Force: 800N~1500N

#### **Tension Device**





Sheave Diameter: \$\phi\$ 200mm; \$\phi\$ 240mm

Wire Rope Nominal diameter: Standard \$ 8mm; Optional \$ 6mm

Weight Type: Barite(High density of ore); Cast iron Installation position: Elevator Pit Guide Rail Side

Traction Machine

Syste

ety Components Series

iidance vstem

(J)

ADIN





Progressive Safety Gear



Instantaneous Safety Gear





Speed	Buffer weight range	Pillar guly riuting	L (mm) free state	Hydraulic oil brand	Oil is needed
≤1.0	600-3000	80	313	HL-46	0.33
≤1.6	600-3000	175	510	HL-46	0.6
≤1.75	600-3000	210	600	HL-46	0.8



Speed	Buffer weight range	Pillar guly riuting	L (mm) free state	Hydraulic oil brand	Oil is needed
≤1.0	300-2500	100	388	HL-46	0.48
≤1.6	700-5300	175	625	HL-46	1.7
≤1.75	1000-5300	290	915	HL-46	2.6



Polyurethane Buffer



Roller Guide Shoe Speed of Applicatiion: ≤2.5m/s



CWT Guide Shoe
Speed of Application: ≤1.75m/s

#### **Guide Shoe**





Sliding guide Shoe Speed of Applicatiion: ≤2.5m/s

#### **Rope Brake**



Triggering mode: over-speed governor upward mechanical triggering of electrical triggering

Reset mode: manually

Functioning position: traction wire rope Installation: upright or upside down


10

# Guidance System

Guidance









#### Hollow Rail





В1	F	H1	К
87	2	60	16.4
87	3	60	16.4

#### Elevator T-shape Rail



Type/Item	А	В	С	D	E	F	G	Н
T75-3/B	10	30	75	3.5	3	2.95	3	62
T89/B	15.88	33.4	89	7.14	6.4	6.37	6.35	62
T90/B	16	42	90	7.14	6.4	6.37	6.35	75
T114/B	16	38	114	7.14	6.4	6.37	6.35	89
T127-1/B	15.88	44.5	127	7.14	6.4	6.37	6.35	88.9
T127-2/B	15.88	50.8	127	7.14	6.4	6.37	6.35	88.9
T140-3/B	31.75	57.2	140	7.14	6.4	6.37	6.35	127

Junction Plate



Skirt Guard Panel



Real Rail Clamp



Glass Holder



Sliding Guide Rail Clamp



# Guidance System

Flanging Hollow Rail Cip







Guide Sleeve



Ripple Reinforcing Rib

Hollow Rail Junction







#### **Elevator Pully/Sheave**







Iron Sheave


#### Note:


- 1: Sheave Diameter: 200~660mm
- 2: Can provide the bearings and shaft as request.
- 3: Can provide some special pulleys/sheaves customized.



## Wire Rope







Nominal Diameter	Approximate Weight kg/100m	Minimum breaking tension of wire rope (KN) (min b/l)						
(mm)		1320/1620N/mm 1410N/mm (Doubel T/S)	1320/1770N/mm 1370/ 1770N/mm 1410N/mm (Doubel T/S)	1570 N/mm (Single T/S)	1620 N/mm (Single T/S)	1770 N/mm (Single T/S)		
8	22.2	26.5	28.1	29.4	30.4	33.2		
9	28.1	33.5	35.6	37.3	38.4	42.0		
9.5	31.3	37.3	39.7	41.5	42.8	46.8		
10	34.7	41.3	44.0	46.0	47.5	51.9		
11	42.0	50.0	53.2	55.6	57.4	62.8		
12	50.0	59.5	63.3	66.2	68.4	74.7		
12.7	56.0	66.6	70.9	74.2	76.6	83.6		
13	58.6	69.8	74.3	77.7	80.2	87.6		
14	67.9	81.0	86.1	90.2	93.0	102.0		
16	88.8	106	113.0	118.0	122	133.0		
19	125.0	149	159.0	168.0	171	187.0		
22	168.0	200	213.0	223.0	230	251.0		



Oil Can



Round Oil Can



Damping Pad



Overload Device



Square Oil Can



Cable Clamp





Door Slider



Fan





**Guilding Device** 





Compensating Chain Device And Accessor



Door Key



Door Lock



Overload Device



Chuck Of Car Top







Damping Pad



Damping Pad



Car Door Switch



Passive Door Switch



Light curtain



Encoder



Passive Door Switch



Governor Switch



limit Switch



Leveling switch



Host interphone for five parties communication



# Cabin

#### Standard type



#### STD-01

Ceiling: Stainless steel frame, acrylic top plate, LED lighting decoration

Car Panel: Hairline stainless steel

Floor: PVC Handrail: Optional



#### STD-02

Ceiling: Painted; LED lighting decoration Car panel: Painted Floor: PVC Handrail: Optional

#### **Superior Type**



#### SUP-01

Ceiling: Stainless steel frame, acrylic top plate, LED

lighting decoration

Car panel: Stainless steel+Mirror etched

Floor: PVC Handrail: Optional



#### SUP-03

Ceiling: Stainless steel frame, acrylic top plate, LED lighting decoration Car panel: Hairline stainless steel

+Mirror etched Floor: PVC Handrail: Optional



#### SUP-02

Ceiling: Mirror stainless steel, LED lighting

decoration

Car panel: Side - Hairline stainless steel, Rear-stainless steel mirror+ Stainless steel

Floor: PVC Handrail: Optional

#### **Deluxe Type**



#### DLX-01

Ceiling: Stainless steel black titanium hairline; Stainless steel mirror roof gilding

spotlight

Car Panel: Stainless steel mirror; Stainless steel black titanium hairline wood cover Front panel: Stainless steel black titanium

hairline

Floor: Marble

Handrails: Stainless steel mirror



#### DLX-02

Ceiling: Stainless steel mirror, LED acrylic

light, tube lamp

Car panel: Combination of rose gold etched stainless steel mirror and etched stainless

steel hairline Floor: Marble

Handrail: Flat handrail

#### **Imperial**



#### IMP-01

Ceiling: Wooden frame painted roof gilding down light Car Panel: Stainless steel mirror wood finishes

Floor: Marble

Handrails: Stainless steel pipe titanium



#### IMP-03

Ceiling: Stainless steel titanium mirror roof gilding spotlight

Car Panel: Stainless steel titanium mirror; Marble

Front panel: Stainless steel titanium mirror

Floor: Mable

Handrails: Stainless steel titanium wooden

handrail



Ceiling: Stainless steel titanium mirror; Stainless steel titanium mirror etching absorb dome light down lamp

Car panel: Stainless steel titanium mirror

Floor: Marble Medallion

Handrails: Stainless steel pipe titanium wood

combination armrest

#### **Door Panel**



D01 Painted



D03 Stainless steel+Glass



D05 Titanium mirror stainless steel



D02 Hairline stainless steel



D04 Stainless steel mirror



D06 Titanium stainless steel

## Ceiling





Handrail



## Floor







F04



F02



F05



F03



F06

#### Cabin for home lift



HL01

Ceiling: Painted; LED lighting

Car panel: Painted

Floor: PVC

Handrail: Optional



HL03

Ceiling: Rose-gold stainless steel, absorb

dome lighting

Front panel: Rose-gold stainless steel
Other panel: Wood veneer

Floor: PVC



HL02

Ceiling: Mirror stainless steel, Acryllic decoration, LED lighting

Front panel: Mirror stainless steel
Two side panel: Stainless steel, Sticker

Rear Panel: Mirror etched stainless steel,

Sticker plate

Floor: PVC



#### HL04

Ceiling: Wood veneer style, Mirror stainless steel, LED lighting Front panel: Hairline stainless steel

Other panel: Wood veneer, Mirror

stainless steel Floor: PVC

Decorative picture : By client

#### Door



HD01 Hairline stainless steel



HD02 Titanium gold stainless steel



HD03 Rose gold stainless steel



HD04 Wood veneer

#### **Cabin for Panorama Lift**



PL01

Car cover: Steel plate spraying with lamp bar Ceiling: Stainless steel frame, acrylic top plate, LED

lighting decoration

Observation panel: Three glue glass of safety clamp Other panel: Hairline stainless steel

Floor: PVC

Handrail: Stainless steel tube



Car cover: Steel plate spraying Observation panel: Three glue glass of

safety clamp

Other panel: Hairline stainless steel

Floor: PVC

Handrail: Stainless steel tube



#### PL03

Car cover: Steel plate spraying

Observation panel: Glue glass of safety clamp

Floor: PVC

Handrail: Stainless steel board



#### PL04

Car cover: White top-down covers of hemispherical acrylic, decorative panel of a painting arc-shaped steel plate, with a number of

decorative light bands

Observation panel: Arc-shaped 5 laminated

glass Floor: PVC

Handrail: Round armrest of stainless steel

#### **Cabin for Freight lift**



#### FL01

Ceiling: Painted steel+LED lighting Car Panel: Painted steel

Floor: Checked steel plate Handrail: Optional

**Cabin for Bed Lift** 



#### BL01

Ceiling: Acrylic lighting decoration, stainless

steel hairline frame

Car Panel: Hairline stainless steel plate

Floor: PVC

Handrail: Optional